

Ground-Effect Specifications

"Spread the word"



Model	GE200	GE300	GE400	GE560	GE650	GE750	GE950	GE1200	GE1300	GE1500	GE1650
Hopper size (capacity) Litres (+/- 2%) (Gal)	200 (53)	300 (79)	400 (106)	560 (148)	650 (171)	750 (198)	950 (251)	1200 (315)	1300 (343)	1500 (396)	1650 (434)
Weight with 6.5hp motor kgs (lb)	40 (44)	75 (165)	90 (198)	93 (204)	112 (218)	113 (248)	120 (264)	123 (270)	127 (279)	152 (334)	168 (370)
Overall Dimension mm (ft)	1080H x 980Ø (42.5"H x 38.5"Ø)	1185H x 850Ø (46.6"H x 33.5"Ø)	1230H x 1085Ø (48.4"H x 42.7"Ø)	1400H x 1085Ø (55"H x 42.7"Ø)	1527H x 1085Ø (60"H x 42.7"Ø)	1445H x 1200Ø (56.8"H x 47.2"Ø)	1610H x 1255Ø (63.3"H x 49.4"Ø)	1630H x 1350Ø (64"H x 53"Ø)	1590H x 1465Ø (62.6"H x 57.7"Ø)	1715H x 1465Ø (67.5"H x 57.7"Ø)	1815H x 1465Ø (71.5"H x 57.7"Ø)
Swath width (granulated fertilizer) - Up to 'X' Meters (Feet)	36 (118)	42 (138)	42 (138)	42 (138)	42 (138)	42 (138)	42 (138)	42 (138)	42 (138)	42 (138)	42 (138)
Empty flight speed (knots)	85.0	90.0	90.0	90.0	90.0	90.0	90.0	85.0	85.0	85.0	85.0

Engines	Power	Torque @ 2500rpm	Fuel capacity	Dry weight	Starter
Motor Honda GCV160	3.3kw (4.4hp)	9.4Nm	1.1 litres	9.8 kgs	Recoil
Motor Honda GSV190	3.8kw (5.1hp)	11.3Nm	2.0 litres	13.2 kgs	Recoil
Motor Honda GXV340	6.6kw (8.9hp)	21.6Nm	2.3 litres	32.3 kgs	Recoil
Motor Honda GXV390	7.6kw (10.2hp)	24.2Nm	2.3 litres	33.3 kgs	Recoil
Motor Honda GXV530	11.3kw (15.2hp)	34.2Nm	5 Litres	30.5kgs	Recoil
Briggs & Stratton 800 Series	4.8kw (6.5hp)	8.25Nm	1.2 Litres	12.2 kgs	Recoil
Briggs & Stratton Intek 13	9.7kw (13hp)		4.4 Litres	31.3kgs	Recoil
Briggs & Stratton Intek 16.5	12.3kw (16.5hp)		4.4 Litres	26.8kgs	Recoil

All buckets come with two lift strops at 6 metres long (19.7 feet). Complete with spreader bar.

Optional extras:
Agitator (Electric or pneumatic)
Retractable legs
Additional orifice plates (6 supplied standard)
Spare vee belt
Liquid Spinner
Electric start
Level probe (s)
Spinner rotation indicator